



**HASTINGS**  
**ADVANCED DECORATING**  
**SYSTEMS INC.**



**SERVING THE PLASTIC  
INDUSTRY SINCE 1988**

## **MODEL P9000**

## **4.5 TON HEAT TRANSFER PRESS**

- ❖ Steel frame construction with large aluminum Work table for ease of mounting tooling.
- ❖ 4 Inch cylinder with anti-pinch point Stroke adjustment
- ❖ Modular plug and play electrical control System
- ❖ Hardened linear shafts and maintenance free Composite die set bearing guide heated head For precise stamping
- ❖ Quick change die mounting plate
- ❖ Four corner die leveling adjustment
- ❖ Operator friendly touch screen controls with totalizer counter, setup button, head up delay before/after transfer index selection, transfer back-up and digital transfer placement
- ❖ Microprocessor controlled press functions
- ❖ Solid state, digital dual display proportioning heat control
- ❖ Two hand anti-tie down buttons with infrared Sensing beams are ergonomically designed to Eliminate physical pressure
- ❖ Press meets Category 3 safety



**1200 C B & H INDUSTRIAL COURT**  
**MANUFACTURERS OF HOT STAMP AND HEAT TRANSFER DECORATING SYSTEMS**  
**P 618-476-6707 F 618-476-6706 SALES@HASTINGSADS.COM**



**HASTINGS**  
**ADVANCED DECORATING**  
**SYSTEMS INC.**



### SPECIAL FEATURES

- **Four corner head leveling adjustment** allows easy die alignment to stamping surface. Dies can be easily leveled to a particular part without the use of shims.
- **Top quality components** are utilized throughout the manufacturing of Hastings ADS products. Electrical, mechanical, and pneumatic components are always standard off-the-shelf components that are readily available. All machined components are painted, nickel plated, or hard anodized for lasting protections.
- **Microprocessors controlled press functions** with touchscreen panel allows operator convenience and repeatable stamping. Standard features include head-up strip delay, before index, film backup, totalizer cycle counter, and setup feature that allows the head to be jogged down. A recipe page allows the operator the convenience of storing up to 10 different part parameters.
- **High accuracy heat transfer index unit** utilizes a two speed system and photoelectric eye sensor that register the witness mark and then make a distance move for fine tuning placement. Front to back fine tuning adjustment eases setup of transfers.
- **Pneumatic system utilizes** high flow components to increase cycle time and efficiency. Pressure regulator and filter control the air flow to the Multi-Power<sup>®</sup> CYLINDER. The multi-stage cylinder generates high force from standard shop air without the need for toggle mechanisms and their inherent problems.

### SPECIFICATIONS

<b>MODEL P9000 4.5 TON PRESS</b>		
<b>HEATED PLATEN SIZE</b>	<b>IMPRINT SIZE</b>	
	8 X 8	8 X 12
<b>ELECTRICAL REQUIREMENTS</b>	240 VAC 10 AMPS	240 VAC 8 AMPS
AIR REQUIREMENTS (PSI)	30 - 100	
HEAD STROKE	0-4	
THROAT DEPTH	10	
ADJUSTABLE DAYLIGHT	0-16	
<b>APPROXIMATE DIMENSIONS</b>		
HEIGHT	92	
WIDTH	49	
DEPTH	36	
WEIGHT (LBS)	850	